



**WHITACRE GREER**  
Quality Since 1900

November 26, 2014

LEED v3 is still in effect for projects registered before October 31, 2016 and completed within six years of the registration date.

Whitacre Greer paving brick may contribute with the following credits:

*MR 5.1 and 5.2 Regional Materials.* The clays and shales used in the manufacture of Whitacre Greer pavers are mined in Northeastern Ohio, near Alliance, OH and within a 500-mile radius of many major metropolitan areas.

*MR 4.1 and 4.2 Recycled Content.* Whitacre Greer pavers have a post consumer recycle content of up to 5.75%. Multi-shade permeable boardwalk pavers are produced with 100% pre-consumer recycled material (ASTM E2129-05).

*SS 7.1 Heat Island Effect Non-roof.* Many of Whitacre Greer paver colors have a SRI of 29 or greater.

<i>Shade</i>	<i>Post Consumer Recycle Content %</i>	<i>SRI</i>
30 Clear Red	1.5	41
32 Antique	1.0	36
33 Dark Antique	1.0	29
34 Mulberry	.75	23
36 Red Sunset	.75	36
38 Old Chicago Cobble	.75	31
41 Caribbean	5.0	49
42 Cinnamon	4.5	45
43 Tangerine	4.0	41
44 Mahogany	2.5	34
50 Ivory	5.75	56
52 Majestic	5.0	44
53 Cimmerian	4.0	34
54 Chocolate	3.0	31
56 Desert Gray	5.0	38
48 Multi-shade Permeable Boardwalk	100% Pre-consumer (ASTM E2129-05)	---

*SS 6.1 and 6.2 Stormwater design/water quality control.* Whitacre Greer permeable pavers can aid in runoff reduction water quality control.

LEED v4 may also be selected to achieve USGBC certification. There are major changes in LEED v4. See Whitacre Greer's LEED v4 data sheet.

1400 South Mahoning Ave.  
Alliance, Ohio 44601

**800 WG PAVER**

P: (330)823-1610

F: (330)823-5502

[www.wgpaver.com](http://www.wgpaver.com)

[info@wgpaver.com](mailto:info@wgpaver.com)