



WHITACRE GREER
CLAY PAVER DETAIL
 BITUMINOUS BED ON REINFORCED CONCRETE BASE
 WITH ASTM CONFORMANCE REQUIREMENTS

GENERAL NOTES:
 - INSTALLER MUST USE STRING LINES AND/OR CHALK LINES TO KEEP PAVER BOND LINES STRAIGHT
 - CONSULT AN ENGINEER FOR HEAVY VEHICULAR APPLICATIONS
 - FOR VEHICULAR USE BEST PRACTICES REQUIRE HERRINGBONE OR CHEVRON PATTERN
 - COMMERCIAL VEHICULAR APPLICATIONS REQUIRE THICKER PAVING UNITS
 * DETAIL PROVIDES GENERAL INFORMATION DRAWN FROM INDUSTRY STANDARDS AND MAY NOT BE APPROPRIATE FOR ALL PAVING APPLICATIONS. CONSULT LOCAL ENGINEERS FOR DESIGN AND CONSTRUCTION INFORMATION APPROPRIATE FOR YOUR AREA

SHEET:	DETAIL 3
SCALE:	1 1/2" = 1'-0"
DATE:	__-__-__
PROJECT:	_____

WHITACRE GREER CLAY PAVER DETAIL (3)
 ALLIANCE, OHIO



DETAIL COMPLETED BY JOSHUA DAVID CINDRICH
 ARCHITECT
 CHICAGO, ILLINOIS 312.852.1220

JUSTIFIED DESIGN collaborative