



Heat Stop® Refractory Mortar Products

Heat Stop® products are used in new installations of firebrick and clay flue lining and also used for repairs. Heat Stop® provides resistance to temperatures well above 2000 deg. F and meets all building codes.

Heat Stop® pre-mixed

Pre-mixed and ready to use as a regular refractory cement. Faster and easier for setting firebrick. Only 1/8" joint required. Water soluble, easy clean up. Gray in color. 15 lb. can or 50 lb. pail.

Domestic Fireplace Mortar

Same as Heat Stop® pre-mixed only beige in color and looser consistency. 15 lb. can or 50 lb. pail.

Heat Stop® II and Heat Stop® 50 dry mix

Best mix for both firebrick and flue installations. Fireplace masons prefer its workability and texture. Sets up fast in wet climates - no efflorescence. Non-Water Soluble in Service. Long shelf life and won't freeze in transit. Ready to use - just add water. Add any mortar color. 10 lb. pail or economical 50 lb bag.

Insul Stick

Combines insulating value and strength for maintenance and repair, paring smoke chambers or repairing clay flues or firebrick. Stronger, advanced composition. Non-water soluble. One gal. or 30 lb. pail.

Heat Cast-40

Castable refractory used to form and pour special shapes, hearth or sidewall or oven dome. One gallon buckets or 40 lb. bags.

Insulating Castable

A light weight, insulating castable refractory used to back up and insulate firebrick, flue liners or clay ovens. Can be poured or troweled. Big 35 lb. bags.

Ceramic Fiber Paper

Used to wrap flue liners to insulate and keep them from bonding with the surrounding masonry. Especially useful in seismic areas if, to save space, the vertical reinforcing steel must be placed between the flue liner and the surrounding masonry. See ASTM C-1283 Clay Flue Lining Installation Standard. 200 square foot rolls (100 foot roll two feet wide, 1/8" thick)

Ask For
The Best! 

Plant:
1400 South Mahoning Ave.
Alliance, OH 44601
P: (330) 823-1610

www.wgpaver.com
Customer Service:
cs1@wgpaver.com
cs2@wgpaver.com

Mailing:
PO Box 2960
Alliance, OH 44601